Journal Publication of International Research for Engineering and Management (JOIREM)
Volume: 01 Issue: 10 | Oct-2023

Vehicle control system implementation Using CAN protocol

Rohit Ingle[1]

Department of Electrical Engineering & K. V. N. Naik Collage of Engineering, Nashik

---***---

Abstract - Present Autos area unit being developed by added of electrical belt for effective operation. usually a vehicle was assembled with associate analog automobilist-vehicle interface for indicating chromatic vehicle standing like speed, energy degree, Engine temperatureetc., This paper presents the event and accomplishment of a digital driving system for asemi-autonomous vehicle to ameliorate the automobilist- vehicle interface. It uses associate ARM grounded knowledge accession system that uses ADC to bring all management knowledge from analog to digital format and vanity through Plasma. The communication module employed in this arrangement is bedded networking by will that has effective knowledge transfer. It conjointly takes feedback of car conditions like Vehicle speed, Engine temperature etc., and management led by main control. additional this unit equipped with GSM that communicates to the holder throughout brink things.

Keywords: eu (Engine management Unit), will (Controller space Network), Bedded C, GSM (Global System for Mobile (communication))

1. INTRODUCTION

With quick dynamical pc and knowledge technology and material of the technology chancing manner into vehicles. they are passing dramatic changes in their capabilities and the way they act with the motorists. though some vehicles have viands for deciding to either effect warnings for the mortal driver or dominant the vehicle autonomously, they usually should build these diagnoses in real time with solely [*fr1] data. So, it is vital that mortal motorists still have some management over the vehicle. Advanced in- vehicle data systems provide vehicles with differing kinds and reaches of intelligence to backstop the driver. The preface into the vehicle style has allowed Associate in Nursing truthful dependent relationship between the driver Associate in Nursingd vehicle by giving a complicated & intelligent motorist- vehicle interface through an intelligent data network. This paper discusses the event of such a bearing frame for the vehicle that is named the digital-driving conduct, that consists of a conjunct expedient between the driver and vehicle for perception, call stuff and management.



Fig 1. Existing and Proposed vehicle control system

Fig. one shows the vehicle management of living and planned system. A vehicle was typically created with associate degree analog motorist- vehicle interface for indicating polychromatic parameters of auto standing like temperature, pressure and speed etc. to reinforce the motorist- vehicle interface, associate degree interactive digital system is intended. A microcontroller adorned information accession system that uses ADC to bring all management information from analog to digital format is employed. Since the in-vehicle data systems square measure detached everywhere the body of a sensible vehicle, a communication module that supports to use a 1 stop management of the vehicle through the master management of the digital driving system.

2. HARDWARE STRUCTURE

The things structure typically integrates the will motor regulator, ARM because the main management module, Tube show at hand Digital interface, GSM for mobile communication and different accessories.

A. CAN bus

1. CAN Bus in an Automobile

will may be a local area network (Transplanted space Network) regulator will motor will transfer the serialized information one by one. Fig two shows a typical infrastructure from associate degree automotive. All players within the will motor subsystems square measure accessible via the management unit on the will motor band for transferring and taking information. will motor is amulti-channel gear mechanism. once a unit fails, it does not have an effect on others. the info transfer rate of will motor in an exceedingly vehicle system is completely different. For representative, the speed of {motor management|control} system and ABS is high speed of real- time control fashion of 125Kbps to 1M rate. While, the speed of movement adaption is low- speed with transmission rate of ten to 125K rate. Others like multimedia system systems use medium- speed rate between the precedent 2.



Fig2. CAN bus system in an Automobile

2. CAN Bus for vehicle drive control System

A typical drive system with the management unit has electronic mechanical system system, transmission systems, antilock braking system (ABS), airbag systems etc. These units square measure the core parts in a very fashionable automotive system. they're sensitive for time and closed to the dependability and security of the complete system. As every management unit for time {period|period of time|period} demand relies on the information update rate and therefore the management period varies, so as to satisfy the period of time needs of every system, it's necessary to attain the implementation of public information sharing, like engine speed, wheel speed, and throttle pedal location. The contents embrace the completion of speed activity, fuel activity, A/D conversion, the calculation conditions, the management mechanism and a series of processes. meaning the causing and receiving information in 1ms should be completed inside the electrical management of fuel so as to attain period of time needs. Therefore, the information exchange network should be a priority-based competitive mode, and features a terribly high speed communication fashion.

3. CAN Bus for accessories control system

CAN bus for vehicle system could be a leading management network that connects many objects. they're central controller, 4- gates controller, memory modules and alternative parts. There ar many things controlled by the will bus [2]. they're locker, windows, bags locker, mirrors and interior dome lightweight. within the case of device, it involves the device signal receiving and process the anti-theft and warning systems.

B. Main control module

1. ARM Architecture

The ARM7TDMI-S may be a general purpose 32- bit microchip, that offers high performance and very low power consumption. The ARM coil is grounded on Reduced Instruction Set pc (RISC) principles. it is the initial computer architecture microchip designed for low- budget decision. one among the everyday product is ARM seven family that is the most efficient computer architecture. So, it's like low-cost, and also the core of ARM7TDMI-S ™ may be a low budget-accustomed, action the management of the system. The ARM7TDMI-S processor conjointly employs a novel field of study strategy referred to as Thumb, that makes it pat suited to high- volume employments with memory restrictions. It will be utilized in a range of areas, akin as bedded management, multimedia, DSP and mobile employments. The LPC2119/ LPC2129 square measure grounded on a16/32 bit ARM7TDMI-S " processor with real- time emulation and bedded trace support, along with128/256 kilobytes (kB) of frozen high speed bash memory.

A 128- bit wide memory interface and a novel accelerator skeleton modify 32- bit law prosecution at most timer rate. It contains a 16/ 32- bit ARM7TDMI-S microcontroller during a itsy-bitsy LQFP64 package. With their compact sixty four leg package, low power consumption, varied 32- bit- channel 10-bit ADC, two advanced will channels, PWM channels, Real Time Timer and Watchdog and forty six GPIO lines with up to nine external intrude legs these microcontrollers square measure notably appropriate for automotive and natural management uses yet as medical systems and fault-tolerant maintenance motors. It does not contain MMU (memory supervising unit). however owing to its low value, trustability and different factors, it's universally utilized in varied natural regulators.

Other accessories

IR detector, Motor speed detector, Alarm, Temperature detector, Pressure detector, Station detector, TV display, GSM modem.



Fig 3. Block diagram of proposed system

Fig three shows the block visual of will vehicle system. It consists of 1 master swelling and 2 slavenodes.ARM because the master regulator (Engine management Module) that controls the vehicle standing with varicolored detectors. 2 Snap ICs square measure used as slave swellings to require the inputs of auto standing. The communication between these detectors is finished by mistreatment will regulator. Slave

Journal Publication of International Research for Engineering and Management (JOIREM)
Volume: 01 Issue: 10 | Oct-2023

regulator receives the signals from vehicles like pressure, temperature, power plant, and IR obstacles and GSMetc., transmit to master regulator with high speed rate. Master controls the standing of auto and sends the feedback to wheelman panel by giving digital information's via receiver show and forewarnings. Presently Operator interface is digital kind. By this wheelman will freely see the signals and fit management the vehicle. IR holdback detector helps in correlating the obstacles presence round the vehicle. Vibration detector detects external force (Hit by different vehicle or mediumetc.,) and sends the signal to GSM. GSM can shoot the dispatch to the owner of the vehicle.

3. SOFTWARE STRUCTURE

The vehicle system is programmed mistreatment the Embedded C and debugged with MPLAB X IDE.



Fig 4. Flowchart for program

Fig 4 shows the flowchart for Embedded C program for vehicle control system using CAN protocol.

4. WORKING MODEL CIRCUITS AND RESULTS



Fig 5. Master circuit

Fig 5 shows the circuit diagram of master node. It consists of Arm LPC2129, Speed detection unit, LCD, Buzzer.



Fig 6. Slave circuit

Fig 6 half-dozen shows the slave circuit. This unit consists a pair of slave unit named as Slave one and Slave a pair of. each slave units square measure PIC 18F4580 regulator. Power stock for each slave units and different detectors square measure five V DC. Slave one unit connected with three detectors. Temperature detector, Pressure detector, Power standing detector. This detector generates analog signal and transport to Slave1 regulator. Slave one regulator changing analog signal into digital signal, either sends to ARM regulator through will MCP2551 regulator. Slave a pair of unit connected with following units. IR stop detector, Vibration detector, Sucker (Vehicle speed), GSM modem.



Fig7. Working model

Fig 7 shows the working model of vehicle control system using CAN.

Results:

Fig 8. Pressure high alarm (More load)

Fig 9. Fuel level low alarm

Fig 10. Obstacle detect alarm



Fig 11. Over speed control OK

The liquid crystal display provided at the driver's panel displays the varied alarms generated with totally different sensors. Alarm throughout the varied cases like high in tyres, stockpile low, Obstacles round the vehicles, Over speed etc., Vibration sensing element receives detects with external impact like accidents, sends the signal to GSM. GSM sends the message to vehicle owner.

5. CONCLUSIONS

This program introduces Associate in Nursing lodged system with a mixture of will motor systems. Digital management of the vehicle is a crucial criterion of current technology. With the fast development of lodged technology, high- performance lodged processor is entered into the motor determination, that is low value, high solidness and different options to fulfill the requirements of the current motor determination. The projected high- speed will motor system solves the matter of automotive system plays, additionally incorporates a sure sensible price and significance. With ARM because the main management and it makes full use of the high- performance of ARM, high- speed reduction of will machine communication management networks and instrument management thus on come through full sharing of knowledge between lumps and enhance their conjunct work. this method options fruitful information transfer among totally different lumps within the sensible operations.

REFERENCES

[1] Kumar, M. A.Verma, and A. Srividya, Response-Time "Modeling of Controller Area Network (CAN). Distributed Computing and Networking, Lecture Notes in Computer Science Volume 5408, p 163-174, 2009.
[2] Tindell, K., A. Burns, and A.J. Wellings, Calculating controller area network (CAN) message response times. Control Engineering Practice, 3(8): p. 1163-1169, 2005.
[3] Li, M., Design of Embedded Remote Temperature Monitoring System based on Advanced RISC Machine. Electrotechnics Electric, 06, p. 273, 2009.
[4] Prodanov, W., M. Valle, and R. Buzas, A controller area network bus transceiver behavioral model for network design and simulation. IEEE Transactions on Industrial Electronics, 56(9): p. 3762-377, 2009.
[5] ISO (1993). Road Vehicles: Interchange of Digital Information: Controller Area Network (CAN) for High Speed Communication. ISO 11898:1993.
[6] B.Gmbh, "CAN specification" vol 1 Version 2.0, 1991.
[7] Pazul, "Controller Area Network (CAN) Basics", Microchip technology Inc., AN713, May 1999.
[8] Wilfried Voss, A comprehensive guide to controller area network, Copperhill Media Corporation, 2005-2008.
[9] Benjamin C Kuo, M. Farid Golnaraghi, Automatic Control systems, Eight edition, John wiley & sons., Inc 2003.